



FORCE America Inc.

# ULTRAKOOL Operator's Manual

FORCE America UK8-40-12VDC-FRM-AL Operator's Manual



# ULTRA KOOL



The High Performance, Compact Cooling System

## Table of Contents

TABLE OF CONTENTS .....	2
UK8-40-12VDC-FRM-AL – MODEL CODE BREAKDOWN .....	3
UK8-40-12VDC-FRM-AL – EXPLODED PARTS VIEW .....	3
UK8-40-12VDC-FRM-AL – BILL OF MATERIALS .....	4
UK8-40-12VDC-FRM-AL – DIMENSIONS .....	5
UK8-40-12VDC-FRM-AL – ELECTRICAL START OPTIONS .....	6
ELECTRICAL KIT COMPONENTS.....	10
UK8-40-12VDC-FRM-AL – TYPICAL PLUMBING LAYOUT.....	11
UK8-40-12VDC-FRM-AL – STARTUP PROCEDURE STEPS.....	12
UK8-40-12VDC-FRM-AL – MAINTENANCE RECOMMENDATIONS.....	13
UK8-40-12VDC-FRM-AL – TROUBLESHOOTING.....	14
UK8-40-12VDC-FRM-AL – PRODUCT INFORMATION.....	15
MA-12 – HYDRAULIC COOLER SPECIFICATIONS .....	16
CONTACT US .....	17


## Warranty Disclaimer

Seller warrants that any goods sold by Seller to Buyer shall be free from defects in material and workmanship for a period of one (1) year from the date of delivery. THIS WARRANTY SHALL BE THE SOLE AND EXCLUSIVE WARRANTY MADE BY SELLER TO BUYER. SELLER HEREBY DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.


# ULTRA KOOL

The High Performance, Compact Cooling System

## UK8-40-12VDC-FRM-AL – Model Code Breakdown



## UK8-40-12VDC-FRM-AL – Exploded Parts View



# ULTRA KOOL



The High Performance, Compact Cooling System


## UK8-40-12VDC-FRM-AL – Bill of Materials

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	1010799	3/8" FLAT WASHER, GENERAL PURPOSE, 18-8 STAINLESS	12
2	1011613	ULTRAKOOL LOGO DECAL	2
3	1011760	WELDMENT, DIFFUSER, 1-1/2 NPT THREAD	1
4	1011765	1/2" FLAT WASHER, USS, ZINC	8
5	1014114	SOCKET HEAD PLUG 3/4 X 16 MALE ORB STEEL	2
6	1014330	ELBOW 1-5/16 X 12 MALE JIC X 1-5/16 X 12 MALE ORB STEEL	1
7	1014331	ELBOW 1-5/16 X 12 MALE JIC X 1-5/8 X 12 MALE ORB STEEL	1
8	1014334	ELBOW 1-5/8 X 12 MALE JIC X 1-5/16 X 12 MALE ORB STEEL	1
9	1015103	3/8" SCREW SIZE SPLIT LOCK WASHER, 0.68" OD, 18-8 STAINLESS	4
10	1015115	#12-14 X 1" SELF DRILLING SCREW, UNSLOTTED HEX WASHER HEAD, ZINC	6
11	1015229	3/8"-16 X 1-1/2" SHCS 18-8 STAINLESS	4
12	1023935	ORING / OLD # 11 70 DURO 2-113-N70	4
13	1031121	MOUNTING KIT FOR 50 GALLON UR50S UPRIGHT RESERVOIR	1
14	1056189	H03631616-16Z-616-616-17.5" CUT	1
15	1068254	SIGHT GAUGE/TEMP 5" METRIC THREAD BLACK ANODIZED	1
16	1087964	GAUGE, FILTER INDICATOR, 0-60 PSI	1
17	1090203	FB-10-00-0 03-0-0	1
18	1090319	RG11, GASKET, TR/TS FILTER, REPLACES O-RING (ZINGA)	1
19	1090428	2"MX1-1/4"F NPT-23GPM-100MESH-3PSI-STEEL BUSH SUC STRAINER	2
20	1090448	71GPM RETURN-24 GPM SUCTION-100PSI MAX-13.28"LENGTH	1
21	1096203	3/8"-16 X 1" SHCS STAINLESS	12
22	1175958	HARNESS, MAIN, COOLER, DEUTSCH, W/ RELAY, 144"	1
23	1200178	MA-12 COOLER, DEUTSCH CONNECTOR, 12VDC FAN, NO BYPASS, AND NO TEMP SENSOR PORT	1
24	1205987	WLDMT, UK FAN COVER, ALUM, PC	1
25	1205988	FFP, UK 12VDC STANDOFF, AL	4
26	1206079	PERFORATED SHEET, .06" THICK, HOLE SIZE .25" SPACING .313", PC BLUE	1
27	1206407	WELDMENT, UK8-40-12VDC, AL, PC	1
28	1206918	NO-SLIP CLIP-ON BARREL NUT 3/8 X 16	4
29	1207215	UK DECAL SHEET - NPT SUCTION DECAL	2
30	1207215	UK DECAL SHEET - DANGER DECAL	2
32	1207215	UK DECAL SHEET - CASE DRAIN DECAL	1

# ULTRA KOOL

The High Performance, Compact Cooling System


## UK8-40-12VDC-FRM-AL – Dimensions




# ULTRA KOOL

The High Performance, Compact Cooling System

## UK8-40-12VDC-FRM-AL – Electrical Start Options




Temperature Switch Fan Activation




Temperature Switch Fan Activation W/Override

# ULTRA KOOL

## The High Performance, Compact Cooling System




**Air Shift PTO Fan Activation**




**Cable Shift PTO Fan Activation**

# ULTRA KOOL

## The High Performance, Compact Cooling System




### Grounding Switch Fan Activation




### Grounding Switch Fan Activation W/Override

# ULTRA KOOL

## The High Performance, Compact Cooling System



### Pressure Switch Fan Activation



### Pressure Switch Fan Activation W/Override

# ULTRA KOOL



The High Performance, Compact Cooling System

## ELECTRICAL KIT COMPONENTS

ITEM	DESCRIPTION	QTY
<b>MAIN HARNESS</b>		
1175958	Harness, Main, Cooler, Deutsch, w/ Relay, 144" (Used with MAR-12-225715)	1.00
<b>PRESSURE SWITCH</b>		
1069985	Pressure Switch, Set 25 PSI, Female Deutsch DT04-2P Connection	1.00
<b>TEMPERATURE SWITCH</b>		
1128418	-8 ORB 120°F Temp Switch, 5/8" Long Probe, N.O., 18" Flying Lead	1.00
<b>PLUG CONNECTOR KIT (DT06-2S)</b>		
1017929	Connector, DT, Plug, 2 Way, Size 16, DT06-2S	1.00
1040708	Deutsch Wedgelock for DT06-2S	1.00
1100400	Deutsch Female Socket, 1062-16-0122	2.00
<b>RECEPTICAL CONNECTOR KIT (DT04-2P)</b>		
1017930	Connector, DT, Receptacle, 2 Way, Size 16, DT04-2P	1.00
1017933	Wedgelock, Receptacle, DT, 2 Way, Size 16, W2P	1.00
1018110	Deutsch male pin, 1060-16-0122	2.00
<b>SAMPLE KIT FOR TEMPURATURE ACTIVATION</b>		
1175958	Harness, Main, Cooler, Deutsch, w/ Relay, 144" (Used with MAR-12-225715)	1.00
1128418	-8 ORB 120°F Temp Switch, 5/8" Long Probe, N.O., 18" Flying Lead	1.00
1017930	Connector, DT, Receptacle, 2 Way, Size 16, DT04-2P	1.00
1017933	Wedgelock, Receptacle, DT, 2 Way, Size 16, W2P	1.00
1018110	Deutsch male pin, 1060-16-0122	2.00

# ULTRA KOOL




11

The High Performance, Compact Cooling System

## UK8-40-12VDC-FRM-AL – Typical Plumbing Layout

# ULTRA KOOL

The High Performance, Compact Cooling System



## UK8-40-12VDC-FRM-AL – Startup Procedure Steps

1. Mount unit to truck chassis.

# ULTRA KOOL



## The High Performance, Compact Cooling System

2. Plumb all hydraulic lines per plumbing diagrams and application diagrams.
3. Fill Reservoir to the high end of the sight gauge.
4. Engage PTO at low RPM levels.
5. Continually add oil to make sure oil level stays visible within the sight gauge.
6. After oil level stays steady check for leaks and repair before continuing.
7. Verify fan operation for either hydraulic or electric fans.
8. Slowly increase PTO speed to get desired pump RPMs.
9. Run system until oil gets to temp (electric) and verify oil is being cooled (both fan types).

Should take roughly 5-10 minutes to verify.

10. Operate all functions of the system to verify the system is properly bled of air.
11. Disengage PTO.
12. System is functional and ready for full operation.

## UK8-40-12VDC-FRM-AL – Maintenance Recommendations

**General** — Look over your Ultra-Kool system before each use to make sure there are no leaks, and all components are good working order.

# ULTRA KOOL



## The High Performance, Compact Cooling System

**Oil** – Replace every 12 months or sooner depending on operational conditions. Only oil based hydraulic fluids should be used in this system. Please contact FORCE America if you have any questions related to the fluid you'd like to use in your system.

**Filters** – Replace as indicated by the gauge on the return filter housing. Replacement filter part number can be obtained from the parts breakdown diagram.

**Hoses** – Replace hoses due to any leaks or a visual inspection revealing abrasions or cracking.

**Cooler** – Rinse every 3-6 months with low pressure water (under 200 PSI). When used in dirty environments, it is recommended to rinse the cooler more frequently for optimal performance.

## UK8-40-12VDC-FRM-AL – Troubleshooting

**Cooling** – If system is not cooling properly check the following items.

- Clean or rinse the cooler to remove debris
- Check to make sure the fan is engaging and functioning properly
- Check for additional heat coming from relief valves not functioning properly
- Check to make sure you don't have pump cavitation in your system

**Noise** – If the system is making excessive noise check the following items.

- Fan is engaging and functioning correctly
- Check oil level is in the center of your sight gauge
- Make sure all bolts are securely fastened on the unit

# ULTRA KOOL



The High Performance, Compact Cooling System

## UK8-40-12VDC-FRM-AL – Product Information

### Technical Specifications:

- Dry weight ..... 70 lbs
- Height ..... 25.15 inches
- Depth ..... 19.81 inches
- Width ..... 20.77 inches
- Oil capacity ..... 8 gallons
- Fan speed ..... 3600 rpm
- Suction port.....2 – 2” NPT
- Drain port.....1 – 8 ORB
- Case Drain.....1 – 8 ORB




# ULTRA KOOL

The High Performance, Compact Cooling System

## MA-12 – Hydraulic Cooler Specifications

MA-12, MA-18, MA-32




Brushless fan option has different dimensions. Consult factory.

Model	A	B	C		F		G	H	J	K		
			Standard	Brushless	Without Bypass Valve	With Bypass Valve				SAE	NPT & BSPP	L
MA-12	13.82 (351)	11.97 (304)	6.36 (162)	6.06 (154)	10.98 (279)	11.86 (301)	5.71 (145)	4.06 (103)	1.00 (25)	#16 SAE	3/4"	4.88 (124)
MA-18	15.84 (402)	14.14 (359)	5.12 (130)	6.2 (157)	12.96 (329)	13.4 (341)	5.87 (149)	4.99 (127)	1.00 (25)	#12 SAE	3/4"	5.91 (150)
MA-32	19.69 (500)	18.46 (469)	6.15 (156)	6.28 (160)	17.30 (439)	17.9 (454)	12.00 (305)	3.84 (98)	1.10 (28)	#16 SAE	1"	8.07 (206)

Note: We reserve the right to make reasonable design changes without notice. All dimensions are in inches (millimeters) unless noted otherwise.

### MA Models - DC Fan Assemblies



Model	DC Amp Draw		Approx. Shipping Weight LBS (KG)
	12V	24V	
MA-3	5.7	3.6	6 (2.72)
MA-3.5	12.5	6.3	9 (4.08)
MA-4	12.5	6.3	16 (7.26)
MA-12	12.5	6.3	19 (8.62)
MA-18	10.6	5.3	23 (10.43)
MA-32	22.2	11.1	28 (12.70)
MA-48	22.2	11.1	45 (20.40)
MA-232	19.3*	9.7*	65 (29.48)
MA-248	19.3*	9.7*	90 (40.80)


\*AMP draw listed as per FAN.

# ULTRA KOOL



The High Performance, Compact Cooling System

## Contact Us



Atlanta, Georgia	888-293-2325	Kansas City, Missouri	800-383-4724
Bismarck, North Dakota	800-624-7568	Memphis, Tennessee	888-845-5876
Charlotte, North Carolina	800-788-8598	Milwaukee, Wisconsin	800-722-5844
Chicago, Illinois	800-433-5765	Minneapolis, Minnesota	800-328-2732
Columbus, Ohio	888-449-0356	Philadelphia, Pennsylvania	800-492-6621
Dallas, Texas	800-893-7225	Salt Lake City, Utah	877-230-0505
Denver, Colorado	888-833-7711	Seattle, Washington	800-354-9028
Fort Dodge, Iowa	800-362-2994		